



Bendix-leading the way in engineering and development of application specific products.

All Bendix® linings meet or exceed FMVSS121.

Our ES 1050 GG lining tames the high temperature and severe duty environments without the normal drum wear and noise sometimes experienced with metallic linings.

ES 1050 is engineered to provide the lowest cost per mile for high axle loads up to a maximum of 29,000 lbs. G.A.W.R., using 18" x 7" extended service brakes with 165 or 180 AL factors as specified in the chart below.

Its outstanding engineering and design provides noise-free results. Even when tested in intense city traffic, ES 1050 showed no evident brake noise.

ES 1050 GG Lining



Applications:

Refuse
Fire Trucks
Tractors used for specialty hauling

Notes:

Available on ES or XLII shoes
High torque but non-aggressive material
Extremely quiet

Market Competition:

Meritor R401, R403
Carlisle MB60
BrakePro CM29
Abex 6040
Fras-le AF587

Size	FMSI	AL Factor	Rolling Radius	Max. G.A.W.R. Single/Tandem	Shoe Type	Bendix Friction
16.5" X 5"	4719	132	19.6"	20k	SAP	ES 1050 GG
16.5" X 5"	4720	132	19.6"	20k	DAP	ES 1050 GG
16.5" X 6"	4725	132	19.6"	20k	SAP	ES 1050 GG
16.5" X 6"	4715	132	19.6"	20k	DAP	ES 1050 GG
16.5" X 7"	4707	180	21.5"	25k / 50k	DAP	ES 1050 GG
16.5" X 7"	4708	180	19.6"	26k / 52k	DAP	ES 1050 GG
16.5" X 7"	4709	180	19.6"	26k / 52k	SAP	ES 1050 GG
16.5" X 8.63"	4711	180	21.5"	25k / 50k	DAP	ES 1050 GG
16.5" X 8.63"	4726	180	19.6"	29k / 58k	SAP	ES 1050 GG
18" X 7"	4527	165 / 180	22.9"	29k	SAP	ES 1050 GG