


FOR MAXIMUM VALUE, DEPEND ON XTRALIFE II™

SPICER®



SPICER XTRA LIFE II S-CAM BRAKES


Award-winning safety. Longer life. Easier maintenance. Parts interchangeability. Maximize the performance of your vehicle's rear and trailer brakes with Spicer's new XtraLife II S-Cam Brakes. Nationally recognized for Excellence in Quality and Productivity, our XtraLife II brakes are designed to exceed the highest safety standards. XtraLife II provides more usable lining volume than standard S-Cam air brakes to extend performance life. Maintenance is made easy with replaceable dual anchor pins for faster brake shoe service. And parts commonality between tractor and trailer brakes of all major manufacturers means reduced inventory, faster training, and simplified service.



TRACTOR BRAKE

Common Parts

- Linings
- Shoes
- Rollers
- Return Spring
- Anchor Springs
- Anchor Pins
- Bushings



TRAILER BRAKE

PREMIUM TAPERED BRAKE LININGS


The Spicer tapered-design brake lining provides maximum material utilization. Spicer brakes ensure longer service life by providing more usable lining volume than standard S-Cam brakes. XtraLife II brakes use FMSI #4707 and #4710 lining blocks commonly found on other long-life brake designs.



DURABLE BRAKE SHOES

All Spicer brake shoes have dual ribs and are precision manufactured to assure proper shoe contour and optimum lining-to-drum contact. In addition, the shoes are fillet welded to provide maximum strength and durability, an important factor to consider when relining brake shoes.

People Finding A Better Way®



S-CAMS

Spicer cams have induction-hardened wear areas that increase cam strength and life.



LIGHTWEIGHT BRAKE SPIDERS

Spicer's newly designed forged steel spiders were developed to reduce overall weight and optimize strength. Oil-impregnated, sintered bronze bushings maximize durability.

BRAKE SHOE SPRINGS

Anchor springs are interchangeable with front, rear, and trailer brakes. The return spring features larger coils for increased strength.



SPICER X TRA LIFE II S-CAM BRAKE SPECIFICATIONS

SIZE: MODEL:	15" x 8.625" XtraLife II	16.5" x 5" XtraLife II	16.5" x 6" XtraLife II	16.5" x 7" XtraLife II
GAW Range	15-20,000	14-16,000	17-19,000	20-23,000
Shoe	Stamped	Stamped	Stamped	Stamped
Spider	Forged	Forged	Forged	Forged
Anchor Pins	Dual	Dual	Dual	Dual
Service	Extended	Extended	Extended	Extended
BRAKE LINING				
FMSI#	4710	4720	4715	4707
Thickness at Center	3/4"	7/8"	7/8"	7/8"
Shape	Tapered Block	Tapered Block	Tapered Block	Tapered Block
Area/Brake (in ²)	233	149	177	208
Wear Volume/Brake (in ³)	90	71	84	98

Discover how Bendix® XtraLife II™ brakes can extend the service life of your brakes. Get all the details. Talk to your Bendix or Roadranger representative. Call 1-866-610-7909 or visit www.foundationbrakes.com today.